



PEAK TORQUE FLUID 50

PREMIUM MINERAL TRANSMISSION OIL

DESCRIPTION & APPLICATION:

PEAK TORQUE FLUID 50 is a heavy-duty transmission fluid formulated for use in power-shift transmissions, drive trains and hydraulic systems in off-highway, earthmoving, mining, logging and farm applications. Suitable to be used in Caterpillar TO-4 and TO-2 applications, Allison C4 and where a monograde SAE 50 transmission oil is specified.

PEAK TORQUE FLUID 50 extends clutch life and assists to eliminate transmission slippage, reduce brake chatter, protect against corrosion and rust. It has excellent compatibility with seals and frictional material, and superior anti-foam characteristics.

BENEFITS:

- Excellent wear protection
- Longer oil life through enhanced oxidation stability
- Prevents transmission slippage
- Protect against rust and corrosion

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.891
Viscosity 40°C cSt	210.3
Viscosity 100°C cSt	18.6
Viscosity Index	98
Flash Point °C	>220
Colour	L 2.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGMTF50020	20 Litre	
PKGMTF50205	205 Litre	
PKGMTF501000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-3
- ✓ Caterpillar TO-4
- ✓ Eaton Vickers EH-1027C
- ✓ Tremec / TTC
- ✓ Komatsu KES 07.868.1
- ✓ ZF TE-ML 01

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 9 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982