



# PEAK ATF DX6

## FULL SYNTHETIC TRANSMISSION FLUID

### PRODUCT DESCRIPTION

PEAK ATF DX6 is formulated using advanced synthetic base oil combined with the latest quality additives to meet the demanding requirements for modern transmission.

PEAK ATF DX6 is designed for use in passenger cars, 4WD's and light commercial vehicles where a low viscosity product is required. This product contains friction modifiers to maintain, desired power transfer and prevent slippage, all while ensuring smooth engagement of clutch plates and bands.

### BENEFITS

- Holds additional torque compared to other low viscosity multi vehicle ATF's
- Extended anti shudder durability
- Extended service life and superior shear stability
- Improved power transfer and fuel economy

### SPECIFICATIONS AND PERFORMANCE LEVEL

- ATF Type 3.1 / Type 3.0
- GM AW-1 / Dexron® VI
- Mitsubishi DiaQueen ATF J3 / ATF PA
- Ford Mercon® LV
- Hyundai/Kia SP-IV / SPH-IV / SP-IV-RR
- Mazda FZ / FW6AEL / 6AXEL
- Aisin Warner JWS 3324
- MB 236.41 / 236.15 / 236.12
- SAAB AW-1
- VAG G 052 533 / VAG G 055 540 (A2) / VAG G 060 162 (A1, A2, A6)
- Chrysler PN 05127382AA / 68043742AA / 68157995AA
- JASO M315-2013 1A-LV
- Nissan Matic S
- Honda ATF DW-1
- Land Rover PN LR0022460LV
- Toyota FZ
- Toyota WS
- Porsche 000 043 304 00
- Shell ATF 134 / ATF 3353
- ZF Life Guard 8 (suitable for use)

### CHARACTERISTICS

Test	Typical Value
Density 15° C g/cm <sup>3</sup>	0.844
Viscosity @ 40°C cSt	28.5
Viscosity @ 100°C cSt	5.9
Viscosity Index	161
Flash Point °C	>210
Colour	Red

### PRODUCT SIZE

Part Number	Size	Carton Qty	Pallet Qty
PKTFDX6001	1 Litre	6	780
PKTFDX6005	5 Litre	4	192
PKTFDX6020	20 Litre		32
PKTFDX6060	60 Litre		9
PKTFDX6205	205 Litre		4
PKTFDX61000	1000 Litre		

PDS published on 29 Oct 2025. Information is correct at time of publishing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

<https://go.lupinsys.com/peaklubricants/harms/pm/3b058c627b36e0171a693d14dfddc5cc-published/attachment/sds.pdf>

Characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability.

