

PEAK ATF DX6

FULL SYNTHETIC TRANSMISSION FLUID

DESCRIPTION & APPLICATION:

PEAK ATF DX6 Fluid uses extremely advanced synthetic base oil combined with the highest quality additives formulated for the latest transmission designs.

PEAK ATF DX6 Fluid is designed for use in passenger cars, 4WD and light commercial vehicles where a low viscosity product is required, this product contains friction modifiers to maintain desired power transfer and prevent slippage, all while ensuring smooth engagement of clutch plates and bands.

BENEFITS:

- Holds additional torque compared to other low viscosity multi vehicle ATFs.
- Extended anti shudder durability.
- Extended service life and superior shear stability.
- Improved power transfer and fuel economy.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.844
Viscosity 40°C cSt	28.50
Viscosity 100°C cSt	5.95
Viscosity Index	161
Flash Point °C	>210
Colour	1.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKTFDX6001	1 Litre	6
PKTFDX6005	5 Litre	4
PKTFDX6020	20 Litre	
PKTFDX6060	60 Litre	
PKTFDX6205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- | | | |
|---|-------------------------------|---|
| ✓ ATF Type 3.0 / Type 3.1 | ✓ Ford Mercon LV | ✓ JWS 3324 |
| ✓ Chrysler P/N 05127382AA / 68043742AA / 68157995AA | ✓ Honda DW-1 | ✓ MB 236.12 / 236.41 |
| ✓ GM AW-1 / Dexron VI | ✓ KIA SP-IV/SPH-IV / SP-IV-RR | ✓ Porsche P/N 000 043 304 00 |
| ✓ JASO 1A-LV / M315-2013 | ✓ Land Rover P/N LR0022460LV | ✓ SAAB AW-1 |
| ✓ Mitsubishi DiaQueen ATF J3 / ATF PA | ✓ Mazda FZ / FW 6AEL / 6AXEL | ✓ Shell 134 / 3353 |
| ✓ Nissan Matic S | ✓ Toyota FZ | ✓ VAG G 052 533 / VAG G 055 540 (A2) / VAG G 060 162 (A1, A2, A6) |
| | ✓ Toyota Type WS | |

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982