



PEAK 0W16

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 0W16 is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring API SP and ILSAC GF-6.

PEAK 0W16 is designed for use in modern naturally aspirated, supercharged & turbocharged petrol, low emission engines and hybrid vehicles.

PEAK 0W16 is recommended for passenger cars, 4WD's and light commercial vehicles where Petrol, E10 and E85 fuels are used.

BENEFITS:

- Improved power and engine responsiveness
- Very high shear stability with a fast-flowing formula
- Specifically formulated for use in GDI and TGDI engines
- Excellent Deposit Control

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.847
Viscosity 40°C cSt	38.1
Viscosity 100°C cSt	7.4
Viscosity Index	165
Flash Point °C	>210
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEF016007	7 Litre	3
PKEF016020	20 Litre	
PKEF016205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

✓ API SP

✓ ILSAC GF-6

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 27 January 2021



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982