

# **PEAK ECO SYN ULTRA SYN VP 50**

## FULL SYNTHETIC VACUUM PUMP OIL

## **DESCRIPTION & APPLICATION:**

PEAK VACUUM PUMP OIL 55 is based on severely hydrocracked base oils chosen for their ability to resist thermal cracking and chemical oxidation at high temperatures, providing superior performance in in vacuum pump cylinders.

PEAK VACUUM PUMP OIL 55 exhibits inherently high oxidation resistance and low chemical reactivity with high resistance to corrosive attack. The combination of low volatility and low vapour pressure delivers extended fluid life.

PEAK VACUUM PUMP OIL 55 is suitable to lubricate rotary vane pumps and recirculating vacuum pumps, cylinders, pump bearings and sealing glands. It is especially suitable for use in lubricating vacuum pumps operating in wet and humid conditions, as found in the dairy industry.

#### **BENEFITS:**

- Excellent demulsibility ensures it readily separates from water providing pump durability
- Good thermal and oxidation stability characteristics permit higher operating temperatures and provides long fluid life.
- Being non-corrosive with a relatively high solvency helps reduce deposit formation keeping internal surfaces cleaner for longer.
- Low vapour pressure minimises the formation of volatile decomposition products.

## **PRODUCT SIZES:**

PRODUCT CODE	PACK SIZE
PKIVACM055020	20 Litre
PKIVACM055205	205 Litre
PKIVACM0551000	1000 Litre

## **TYPICAL CHARACTERISTICS\*:**

TEST	TYPICAL VALUE
Density 15° C g/cm³	0.870
Viscosity 40°C cSt	54.2
Viscosity 100°C cSt	7.6
Viscosity Index	102
Flash Point °C	>220

### **SPECIFICATIONS & PERFORMANCE LEVEL:**

 $Health, safety\ and\ environmental\ information\ is\ provided\ on\ the\ Safety\ Data\ Sheet\ (SDS)\ for\ this\ product.$ 

Published 28 October 2021

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



