



PEAK JAY 2

SPECIALTY SPINDLE OIL

DESCRIPTION & APPLICATION:

PEAK JAY 2 is a low viscosity premium quality isoparaffinic based spindle oil. It will provide protection against rusting, oxidation and corrosion and is suitable for lubricating high speed bearings, needles and spindles requiring a non-zinc anti wear oil.

PEAK JAY 2 is designed to meet specifications requiring a premium quality, light viscosity fluid for applications running at high speeds such as those found in high speed frames and automated machine tools. It is particularly recommended for spindle bearings operating with exceptionally close tolerances.

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil life and lower maintenance costs
- Low viscosity for the smooth running of high-speed machine elements and to minimise heat build-up through frictional energy losses.
- Non- Zinc anti-wear additives make it suitable for use in circulating systems where silver plated components may be present

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.803
Viscosity @ 40°C cSt	ASTM D7042	2.1
Total Acid Number mgKOH/g	ASTM D974	0.06
Pour Point °C	ASTM D97	-35
Flash Point °C	ASTM D92	>80

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIMM002020	20 Litre	
PKIMM002205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

✓ ISO VG 2

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 July 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982