

PEAK C4 5W30

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK C4 5W30 is a low-SAPS / Low Ash synthetic engine oil formulated to meet the demands and fuel efficiency expectations of the latest diesel engines, suitable for use where ACEA C4, MB 229.51 and Renault RN0720 are required.

PEAK C4 5W30 is recommended for use in modern turbocharged, supercharged and naturally aspirated diesel engines fitted with Diesel Particulate Filters (DPF)

BENEFITS:

- Excellent soot and sludge control
- Extended engine oil drain intervals.
- Low SAPS (Sulphated Ash, Phosphorus and Sulphur).
- Outstanding low temperature performance for reduced wear on start-up.

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.847
Kinetic Viscosity @ 40°C cSt	ASTM D7042	66.0
Kinetic Viscosity @ 100°C cSt	ASTM D7042	11.71
Viscosity Index	ASTM D2270	173.0
Flash Point °C	ASTM D92	>215
Sulphated Ash	ASTM D874	0.5
Colour	ASTM 1500	L 2.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEFC4530005	5 Litre	4
PKEFC4530010	10 Litre	
PKEFC4530020	20 Litre	
PKEFC4530205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ACEA C4 -12
- ✓ MB-Approval 229.51
- ✓ MB-Approval 226.51
- ✓ Renault RN0720

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 20 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982