



PEAK CATTLE ANTI-BLOAT OIL

CATTLE ANTI-BLOAT EMULSIFIABLE OIL

DESCRIPTION & APPLICATION:

PEAK CATTLE ANTI-BLOAT OIL is a specially formulated blend developed for the prevention, control and treatment of bloat in cattle. The ingredients are safe and palatable to animals.

PEAK CATTLE ANTI-BLOAT OIL forms a white emulsion for use as a Flank Lick, Oral Drench, Pasture Spray, Bail Feed, and Drinking Trough preparation when mixed correctly with water.

BENEFITS:

- Ingredients are safe and palatable to animals
- Forms a stable emulsion when mixed with water.
- Can be applied by Flank Lick, Oral Drench, Pasture Spray, Bail Feed and Drinking Trough Preparation

TYPICAL CHARACTERISTICS*

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.844
Viscosity 40°C cSt	17.90
Flash Point °C	>200

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE
PKSMCBW020	20 Litre
PKSMCBW205	205 Litre

DIRECTIONS FOR USE:

Flank Lick: Apply 70ml of Peak Anti-Bloat White Oil undiluted per animal at each milking to the ribs/flank using a paint brush or spray bottle.

Oral Drench (Recommended method): Apply as a drench at a rate 70ml of Peak Anti-Bloat White Oil undiluted per animal usually at milking times.

Pasture Drench: The use of a boom spray is recommended to ensure optimum coverage, penetration and to minimise losses due to wind drift. Peak Anti-Bloat White Oil will wash off with heavy rain. Re-spraying is necessary as soon as possible.

Mixing: The spray tank should be half filled with water, then with the agitator operating the required quantity Peak Anti-Bloat White Oil should be added to the tank followed by the remainder of water. Re-circulation should continue until completion of spraying. To re-emulsify the solution, re-circulate through the pump or stir vigorously in the holding tank.

Application: Apply 90 mls of Peak Anti-Bloat White Oil per head per day through a Boom Spray. (4.5 litres will protect 50 animals per day). Mix the required amount thoroughly with water to cover one day's grazing.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982



For typical grazing situations Peak Anti-Bloat White Oil can be made up as follows:

Mix 4.5 litres of Peak Anti-Bloat White Oil with 95 litres of clean water to cover an area to be grazed by 50 cows per day. To ensure adequate penetration on pastures which have been idle and show heavy growth, the amount of Peak Anti-Bloat White Oil used may need to be greater than 4.5 litres in 95 litres of water. Conversely, less Peak Anti-Bloat White Oil than 4.5 litres per 95 litres of water may be required on paddocks which have a lower animal feeding capacity.

Grazing: Strip grazing with the use of electric fences of the selected pasture will simplify the spraying requirements and thereby assist in controlling bloat. Ensure that all the selected pasture is adequately treated including those areas that can be reached outside the fence line. Avoid back grazing as young shoots that are not treated are bloat inducing.

Bail Feed: Apply directly to feed bails. Dilute with water for ease of application and to facilitate dosage. Recommended rate is 90 mls of Peak Anti-Bloat White Oil per head of cattle.

Drinking Trough: Peak Anti-Bloat White Oil can be mixed with cattle drinking water. Calculate the untreated water capacity of the trough and top up as necessary. Always add the Peak Anti-Bloat White Oil to the filled trough in the desired treat rate. First add water to the trough, then add the desired dose of Peak Anti-Bloat White Oil and mix thoroughly.

Application: Add the required amount of Peak Anti-Bloat White Oil. e.g. 4.5 litres to 95 litres of water in the trough.

Stir well to form a stable solution

WATER HARDNESS: The emulsifier package in Peak Anti-Bloat White Oil ensures a stable emulsion in both soft & hard water, however, if on the initial fill of Anti-Bloat White Oil to water, the emulsion is not stable, increase the treat rate to 6lts to 95lts of water and then mix thoroughly.

IMPORTANT: Do not premix and always add Peak Anti-Bloat White Oil to water.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 15 November 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



**Proudly Australian Owned
Since 1982**