

STELLA™ GEAR OIL FG

FOOD GRADE GEAR OILS

DESCRIPTION & APPLICATION:

STELLA™ GEAR OIL FG OILS are full synthetic food grade oils suitable for the lubrication of gearboxes and reduction units.

STELLA™ GEAR OIL FG Oils are NSF H1 registered for use where incidental contact with food may occur in food, drink and pharmaceutical processing and packaging equipment

STELLA™ GEAR OIL FG OILS provide outstanding lubrication in all enclosed gears operating under normal or heavy shock-loading conditions. They deliver outstanding anti-wear protection and corrosion protection even in the presence of moisture.

BENEFITS:

- Outstanding anti-wear protection
- Excellent corrosion resistance even in the presence of moisture
- Longer oil life due to the exceptional chemical and thermal stability
- Excellent water separation characteristics
- Safe for use in HACCP Certified Food and Packaging Manufacturing Plants

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE		
PKIGFG150	5, 20, 205 Litre		
PKIGFG220	5, 20, 205 Litre		
PKIGFG320	5, 20, 205 Litre		
PKIGFG460	5, 20, 205 Litre		

TYPICAL CHARACTERISTICS*:

TEST	150	220	320	460
Density 15° C g/cm ³	0.845	0.849	0.853	0.856
Kinetic Viscosity @ 40°C cSt	150	220	320	460
Kinetic Viscosity @ 100°C cSt	19.6	25.6	33.8	43.8
Viscosity Index	150	148	148	148
Flash Point °C	>240	>240	>250	>250
Pour Point °C	-35	-35	-30	-30

SPECIFICATIONS & PERFORMANCE LEVEL:

✓ NSF H1 registered

Stella™ is a trademark of Food Grade Oils Pty Ltd

 $Health, safety\ and\ environmental\ information\ is\ provided\ on\ the\ Safety\ Data\ Sheet\ (SDS)\ for\ this\ product.$

Published 19 August 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



