



STELLA™ GEAR OIL FG - GEARGUARD

FOOD GRADE GEAR OILS

DESCRIPTION & APPLICATION:

STELLA™ GEAR OIL FG – GEARGUARD are a range of Semi-Synthetic food grade gear oils particularly suited for the lubrication of gearboxes and reduction units.

STELLA™ GEAR OIL FG – GEARGUARD contains special additives that extend re-lubrication intervals.

STELLA™ GEAR OIL FG – GEARGUARD Oils are NSF H1 registered for use where incidental contact with food may occur in food, drink and pharmaceutical processing and packaging equipment

BENEFITS:

- Outstanding anti-wear protection
- Excellent corrosion resistance even in the presence of moisture
- Very good oxidation stability which extends lubricant life
- Excellent water separation characteristics
- Safe for use in HACCP Certified Food and Packaging Manufacturing Plants

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE
PKIGFGS150	20 Litre
PKIGFGS220	20 Litre
PKIGFGS320	20 Litre
PKIGFGS460	20 Litre

TYPICAL CHARACTERISTICS*:

TEST	150	220	320	460
Density 15°C g/cm ³	0.866	0.870	0.875	0.879
Kinetic Viscosity @ 40°C cSt	150	220	320	460
Kinetic Viscosity @ 100°C cSt	15.9	20.6	26.7	34.2
Viscosity Index	110	110	110	110
FZG Gear Test Stage, Pass	12	12	12	12
Flash Point °C	>230	>230	>230	>250
Pour Point °C	-15	-15	-15	-12

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ NSF H1 registered

Stella™ is a trademark of Food Grade Oils Pty Ltd

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 2 September 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982