

PEAK HD TRUCK COOL

HEAVY DUTY COOLANT

DESCRIPTION & APPLICATION:

PEAK HD Truck Cool is a Ethylene Glycol based engine coolant containing a balanced mixture of organic acid and inorganic corrosion inhibitors specially designed to service the requirements of a broad range of heavy duty diesel engines, particularly those with wet sleeve cylinder liners.

PEAK HD Truck Cool is a low silicate, phosphate and amine free formulation providing long service life and excellent corrosion protection for aluminium, yellow metal and ferrous alloys. It is particularly recommended for wet liner engines operating in both on-highway and off-road environments and arduous city stop-start driving conditions.

BENEFITS:

- Low silicate, phosphate and amine free
- Does not require an initial charge of Supplemental Coolant Additive (SCA), however SCAs may be added as part of a planned maintenance schedule.
- Compatible with most commercial SCAs Product is compatible with other traditional fully formulated engine coolants
- Compatible with all conventional hoses, gaskets, seals and plastics used in heavy duty engine cooling systems

DOSE RATE - FREEZING POINT - BOILING POINT

Mixture ratio	33%	50%	
Freezing Point °C	-18	-35	
Boiling Point °C	103	109	

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE	
Density 15°C g/cm³	1.05	
Colour	Green/Red	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ASTM D3306, D4985
- ✓ Caterpillar (other than EC-1)
- ✓ Cummins 14603

- ✓ Mack
- ✓ Kenworth R)26-170-97
- ✓ Freightliner 48-22880

PRODUCT SIZES:

I RODUCT SIZES.			
PRODUCT CODE	PACK SIZE	CTN QTY	
PKRHDT005	5 Litre	4	
PKRHDT020	20 Litre		
PKRHDT205	205 Litre		

 $Health, safety\ and\ environmental\ information\ is\ provided\ on\ the\ Safety\ Data\ Sheet\ (SDS)\ for\ this\ product.$

Published 13 July 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.





ABN: 74 8875 10101

