

# PEAK FARM OIL

## PREMIUM MINERAL STOU OIL

### DESCRIPTION & APPLICATION:

PEAK Farm oil is a premium mineral Super Tractor Oil Universal (STOU) manufactured using refined base oils and a high-quality additive package which reduces the range of lubricants required on a farm, without sacrificing lubrication, protection, and equipment performance.

PEAK Farm oil is a multipurpose lubricant suitable for a wide range of farming vehicles and equipment. It can be used in petrol and diesel engines, transmissions, oil immersed wet brakes, and hydraulic systems associated with powered and PTO equipment used in the agricultural industry.

### BENEFITS:

- Can be used in Petrol & Diesel applications
- Reduces inventory costs
- One oil for wet brakes, hydraulic, transmission and engine applications
- Reduces the chance of misapplication
- Minimises brake squawk

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	0.870
Viscosity 40°C cSt	97.5
Viscosity 100°C cSt	13.1
Viscosity Index	132
Flash Point °C	>210
Colour	Dark Brown

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDMFO005	5 Litre	4
PKDMFO020	20 Litre	
PKDMFO205	205 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

- |                          |                            |                            |
|--------------------------|----------------------------|----------------------------|
| ✓ SAE 15W40              | ✓ John Deere J27           | ✓ John Deere J20C          |
| ✓ API SF                 | ✓ Massey Ferguson CMS      | ✓ John Deere J27           |
| ✓ API CG-4               | M1145 / 1144 / 1139        | ✓ Ford M2C134D             |
| ✓ API GL-4               | ✓ New Holland 82009201/2/3 | ✓ Case New Holland MAT3525 |
| ✓ ACEA E3                | ✓ ZF TE ML 06A/B/C & 07B   | / 3526                     |
| ✓ Ford M2C 159B/C & 3526 |                            |                            |

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

#### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982