



PEAK 10W30

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 10W30 is a premium quality engine oil formulated with a combination of synthetic and conventional base oils and high-performance additives making it suitable for engines requiring API SN / SM and ILSAC GF-5.

PEAK 10W30 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter. This product is also suitable for use where vehicles are using E85 / E10 Ethanol fuels and for hybrid vehicles.

BENEFITS:

- Outstanding thermal and oxidation stability
- Excellent detergent additives to improved engine cleanliness
- Engine seals stay soft and pliable to minimize and reduce oil leakages

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.865
Viscosity 40°C cSt	76.8
Viscosity 100°C cSt	11.8
Viscosity Index	149.3
Flash Point °C	>205
Colour	L 3.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKES1030001	1 Litre	6
PKES1030005	5 Litre	4

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN / SM
- ✓ ILSAC GF-5

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 9 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982