



PEAK PERFORMANCE DIESEL 15W40

PREMIUM MINERAL DIESEL OIL

DESCRIPTION & APPLICATION:

PEAK PERFORMANCE DIESEL 15W40 is a multi-grade diesel engine oil formulated to provide outstanding protection for diesel engines used in the toughest on and off-road applications.

PEAK PERFORMANCE DIESEL 15W40 is recommended for vehicles where performance specifications API CH-4 / SJ and Volvo VDS-3. Is suitable for use in diesel, passenger cars, 4WD's, light & heavy-duty commercial engines in trucks, tractors, agricultural & earthmoving, forklifts and stationary engines. It is also suitable for Petrol, E10 and LPG.

BENEFITS:

- Excellent detergent and dispersant additives for a cleaner engine.
- Unique viscosity control additives prevent thickening of the oil.
- Very high shear stability resulting in superior load carrying ability.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.879
Viscosity 40°C cSt	104
Viscosity 100°C cSt	14
Viscosity Index	137
Flash Point °C	>220
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKDM1540005	5 Litre	4
PKDM1540020	20 Litre	
PKDM1540205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API CH-4 / SJ
- ✓ ACEA E7 -12
- ✓ MB 228.3
- ✓ Volvo VDS-3
- ✓ Mack EO-N / M Plus
- ✓ MAN M3275
- ✓ Cummins CES 20076 / 20077
- ✓ Renault Truck RLD-2
- ✓ MTU Type 2
- ✓ Detroit Diesel DDC 93K215
- ✓ CAT ECF-1A

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 27 June 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982