



PEAK SYNGEAR ULTRA 75W85

FULL SYNTHETIC GEAR OIL

DESCRIPTION & APPLICATION:

PEAK SYNGEAR ULTRA 75W85 is a full synthetic gear oil meeting API GL-5 specially formulated for use in automotive light duty and heavy-duty axles and heavy duty non-synchronized transmissions.

PEAK SYNGEAR ULTRA 75W85 is recommended for vehicles calling for a 75W85 GL-5 including vehicles with limited slip differential. It is also suitable in manual transmissions calling for 75W85 GL-5.

Please note vehicles requiring 75W85 GL4 we recommend PEAK 75W85 (PKGS7585).

BENEFITS:

- Superior wear protection for prolonged equipment life.
- Excellent shear stability allowing for longer lubricant life resulting in extended drain intervals
- Outstanding resistance to corrosion and oil degradation.

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKG7585002.5	2.5 Litre	6
PKG7585020	20 Litre	
PKG7585205	205 Litre	

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.863
Viscosity 40°C cSt	76.4
Viscosity 100°C cSt	13.01
Viscosity Index	172.2
Flash Point °C	>205

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-5
- ✓ API MT-1
- ✓ MB 235.74
- ✓ PG-2 LIMITED SLIP
- ✓ MIL-PRF-2105D / MIL-PRF-2105E
- ✓ SAE J2360

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 12 December 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982