



PEAK 5W40 SP A3/B4

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W40 SP A3/B4 is a premium synthetic engine oil formulated to meet both the latest API SP specification and the European ACEA A3/B4 requirements.

PEAK 5W40 SP is recommended for use in modern multi-cam, multi-valve, turbocharged, supercharged and naturally aspirated petrol engines.

BENEFITS:

- Excellent sludge and deposit control.
- Outstanding low temperature performance for reduced wear on start-up.
- Improved engine resilience and fuel economy
- Reduction in oil consumption.
- Improved Low Speed Pre-Ignition (LSPI) protection

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.853
Viscosity 40°C cSt	80.6
Viscosity 100°C cSt	13.6
Viscosity Index	170
Flash Point °C	>215
Colour	L 3.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEF540007	7 Litre	3
PKEF540020	20 Litre	
PKEF540205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SP
- ✓ ACEA A3/B4-20
- ✓ BMW Longlife – 01
- ✓ MB-Approval 229.5
- ✓ VW 502.00 / 505.00
- ✓ PSA B71 2296
- ✓ Porsche A40
- ✓ Renault RN 0700 / RN 0710

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 11 August 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982