

PEAK NEAT CUT 32

NEAT CUTTING OIL

DESCRIPTION & APPLICATION:

PEAK NEAT CUT 32 is an inactive type cutting oil formulated with refined paraffinic base oils. It is an excellent dual-purpose cutting and lubricating oil for higher speed machining of free cutting steels; brass, aluminium, copper, etc. in multiple spindle automatics.

PEAK NEAT CUT 32 acts as both a machine lubricant and a cutting oil where a lower viscosity oil is required. For eg. higher speed machining of free cutting steels such as brass, aluminium, copper and other softer type metals.

FEATURES & BENEFITS:

- Serves as both a machine lubricant and a cutting oil
- Longer tool life tool life and improved surface finish,
- Non active formulation makes it suitable for copper based alloys

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.850
Kinetic Viscosity @ 40°C cSt	32.0
Flash Point °C	>180

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKICMNC32020	20 Litre	
PKICMNC32205	205 Litre	
PKICMNC321000	1000 Litre	

APPLICATION :

- Used neat.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 21 March 2022

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982