



PEAK JAY 150

PREMIUM MINERAL CIRCULATING OIL

DESCRIPTION & APPLICATION:

PEAK BRAE 150 is a medium viscosity high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion, It is suitable to be used in large, slow-speed bearings in mixers and mills.

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil life and lower maintenance costs
- Excellent demulsibility characteristics which allow these oils to maintain a high film strength coating on critical wear points of bearings and gear reducers and assure fast removal of water contamination
- Non-Zinc anti-wear additives make it suitable for use in circulating systems where silver plated components may be present

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.885
Viscosity @ 40°C cSt	ASTM D7042	150
Viscosity @ 100°C cSt	ASTM D7042	15.5
Viscosity Index	ASTM D2270	105
Flash Point °C	ASTM D92	>220

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIMM150020	20 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ DIN 51517-1 Type C
- ✓ DIN 51517-2 Type CL

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 6 April 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



**Proudly Australian Owned
Since 1982**