



PEAK JAY 68

PREMIUM MINERAL CIRCULATING OIL

DESCRIPTION & APPLICATION:

PEAK JAY 68 is a low viscosity high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion, It is suitable to be used as a hydraulic oil where anti-wear performance is less critical. It can also be used for vacuum pumps where a VG68 is specified.

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil life and lower maintenance costs
- Excellent demulsibility characteristics which allow these oils to maintain a high film strength coating on critical wear points of bearings and gear reducers and assure fast removal of water contamination
- Non Zinc anti-wear additives make it suitable for use in circulating systems where silver plated components may be present

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.872
Viscosity @ 40°C cSt	66.9
Viscosity @ 100°C cSt	8.9
Viscosity Index	107
Flash Point °C	>200

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIMM068020	20 Litre	
PKIMM068205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Cincinnati Machine P-54

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 September 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



**Proudly Australian Owned
Since 1982**