

PEAK BRAKE FLUID DOT 3

HIGH PERFORMANCE BRAKE FLUID

DESCRIPTION & APPLICATION:

PEAK BRAKE FLUID DOT 3 is a premium, high performance, high boiling point heavy duty brake fluid for superior performance in conventional disc and drum brake requiring FMVSS No 166 DOT 3, ISO 4925 Class 3, SAE J 1703, JIS K 2233 Class 3 and AS/NZ 1960 Class 1 fluid.

BENEFITS:

- Extremely high boiling points delivering optimum performance of the brake system
- Excellent low temperature viscosity resulting in an improvement in the brake response behaviour
- Corrosion Protection through a specially formulated Inhibitor Package
- Optimal Lubricity which avoids the abrasion of the brake system by friction.
- High Elastomer Compatibility providing an improvement in Brake fluid loss.

Note: Do not use in hydraulic/brake systems where DOT4 and DOT 5 (Silicone Brake Fluid) are specified.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE	
Density 20°C g/ml	1.063	
Viscosity -40°C cSt	980	
ERBP °C	270	
Wet ERBP °C	154	
pH Value	9.7	

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKBFD3001	1 Litre	6
PKBFD3005	5 Litre	4
PKBFD3020	20 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ DOT 3
- ✓ ISO 4925 Class 3
- ✓ SAE J1703

- ✓ JIS K 2233 Class 3
- ✓ FMVSS No DOT 3
- ✓ AS/NZ 1960 Class 1

 $Health, safety\ and\ environmental\ information\ is\ provided\ on\ the\ Safety\ Data\ Sheet\ (SDS)\ for\ this\ product.$

Published 28 July 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.



