



PEAK AIR TOOL OIL

PREMIUM MINERAL - ISO 46

DESCRIPTION & APPLICATION:

PEAK Air Tool Oil is a mineral based lubricant with anti-wear, oxidation and corrosion inhibitors, anti-foam additives. It is a thermally stable fluid capable of handling high loads and temperatures and is designed for lubricating the internal parts of pneumatic air tools. It also has excellent water separation and hydrolytic stability for prolonged lubricant life and improved equipment performance.

PEAK Air Tool Oil is suitable for most air tools and will extend the life of your air ratchet, air drill, impact wrench, air chisel and other air tools.

BENEFITS:

- Provides excellent wear and corrosion protection
- Extends tool life
- Enhanced air release and anti-foam properties prevent cavitation
- Excellent filterability prevents filter blockages

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.858
Viscosity 40°C cSt	46.0
Viscosity 100°C cSt	7.2
Viscosity Index	119
Flash Point °C	>205
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKSAT005	5 Litre	4
PKSAT020	20 Litre	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 17 April 2023



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982