



PEAK TORA 100

MINERAL INDUSTRIAL GEAR OIL

DESCRIPTION & APPLICATION:

PEAK TORA 100 is a high-quality extreme pressure ISO 100 industrial gear oil. It is suitable for use in enclosed gearboxes in industrial applications and may be used for plain bearings where high loadings or stresses are encountered.

PEAK TORA 100 may be used for the lubrication of spur and helical gears, and some constantly loaded worm type gear applications.

BENEFITS:

- Excellent wear and corrosion protection, ensuring good equipment life and decreased downtime.
- Extreme Pressure (EP) performance protects gears against wear and shock loading.
- Enhanced air release and anti-foam properties that prevent cavitation.
- Compatible with most common types of seal materials.
- Good water separation and hydrolytic stability means reduced downtime through prolonged lubricant life and improved equipment performance.

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.875
Viscosity @ 40°C cSt	ASTM D7042	93.3
Viscosity @ 100°C cSt	ASTM D7042	11.5
Viscosity Index	ASTM D2270	112
Flash Point °C	ASTM D92	>230

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIGM0100020	20 Litre	
PKIGM0100205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-4
- ✓ US Steel 224
- ✓ AGMA 9005-E02
- ✓ DIN 51517-3 (CLP)
- ✓ David Brown S1.53.101 (TYPE E)

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 30 March 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982