



PEAK 5W30 ULTRA

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W30 ULTRA is specifically formulated with synthetic base stocks matched with high-performance additives to create the finest quality engine oil for modern engines.

PEAK 5W30 ULTRA is especially targeted to VW 504 00 and 507 00 specifications for Volkswagen, Audi, Skoda and Seat vehicles for both petrol and diesel engines. PEAK 5W30 ULTRA is suitable for modern diesel vehicles fitted with Diesel Particulate Filters (DPF), petrol and hybrid engines. It provides superior protection against engine damage caused by LSPI.

BENEFITS:

- Extended engine oil drain intervals.
- Mid SAPS (Sulphated Ash, Phosphorus and Sulphur).
- Superior oxidation control and thermal stability.
- Excellent wear protection, minimum sludge formation and reduced piston deposits.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.852
Viscosity 40°C cSt	69.9
Viscosity 100°C cSt	12.2
Viscosity Index	173
Flash Point °C	>210
Sulphated Ash	0.8
Colour	L 3.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEF530U005	5 Litre	4
PKEF530U007	7 Litre	3
PKEF530U010	10 Litre	
PKEF530U020	20 Litre	
PKEF530U205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SP
- ✓ VW 504 00 / 507 00
- ✓ BMW LL-04
- ✓ MB 229.52 / 51/ 31
- ✓ ACEA C3 -16
- ✓ Porsche C30
- ✓ OPAL OV0401547

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 27 January 2021



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982