

PEAK 5W30 ULTRA

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W30 ULTRA is specifically formulated with PAO base stocks matched with high-performance additives to create the finest quality engine oil for modern engines.

PEAK 5W30 ULTRA is suitable for use where VW 504 00 and VW 507 00 specifications for Volkswagen, Audi, Skoda and Seat vehicles are required for both petrol and diesel engines.

PEAK 5W30 ULTRA is suitable for modern diesel vehicles fitted with Diesel Particulate Filters (DPF), petrol and hybrid engines.

BENEFITS:

- Extended engine oil drain intervals.
- Low SAPS (Sulphated Ash, Phosphorus and Sulphur).
- Superior oxidation control and thermal stability.
- Excellent wear protection, minimum sludge formation and reduced piston deposits.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.852
Viscosity 40°C cSt	56.0
Viscosity 100°C cSt	10.4
Viscosity Index	173
Flash Point °C	>210
Sulphated Ash	0.8
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEF530U005	5 Litre	4
PKEF530U010	10 Litre	
PKEF530U020	20 Litre	
PKEF530U060	60 Litre	
PKEF530U205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- | | |
|----------------------|---------------|
| ✓ API SN | ✓ ACEA C3 -16 |
| ✓ VW 504 00 / 507 00 | ✓ Porsche C30 |
| ✓ BMW LL-04 | ✓ VW TL 52195 |
| ✓ MB 229.51 | |

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982