

PEAK SEMI SYNTHETIC 15W50

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK Semi Synthetic 15W50 is a premium quality engine oil formulated with a combination of synthetic and conventional base oils along with high-performance additives making it suitable for engines requiring API SN, ACEA A3 / B4.

PEAK Semi Synthetic 15W50 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter. This product is also suitable for use in LPG / dual fuel and diesel applications.

BENEFITS:

- Outstanding thermal and oxidation stability
- Excellent detergent additives for improved engine cleanliness
- Engine seals stay soft and pliable to minimize and reduce oil leakages
- Outstanding shear stability

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.875
Viscosity 40°C cSt	163.5
Viscosity 100°C cSt	19.8
Viscosity Index	140
Flash Point °C	>220
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKES1550005	5 Litre	4
PKES1550020	20 Litre	
PKES1550205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN / CF
- ✓ ACEA A3 / B4 -12
- ✓ MB-Approval 229.1
- ✓ VW 501 01 / 505 00

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 23 April 2021

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982