

PEAK 10W40

SEMI SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 10W40 is a premium quality engine oil formulated with a combination of synthetic and conventional base oils and high-performance additives making it suitable for engines requiring API SN and ACEA A3 / B4.

PEAK 10W40 is recommended for petrol engines (multivalve and turbo) with or without a catalytic converter. This product is suitable for diesel and hybrid vehicles.

BENEFITS:

- Engine seals stay soft and pliable to minimise and reduce oil leakages
- Excellent detergent additives to improve engine cleanliness
- Outstanding thermal and oxidation stability

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.869
Viscosity 40°C cSt	90.4
Viscosity 100°C cSt	13.3
Viscosity Index	148
Flash Point °C	>210
Colour	L 2.5

PRODUCT SIZES

PRODUCT CODE	PACK SIZE	CTN QTY
PKES1040001	1 Litre	6
PKES1040005	5 Litre	4
PKES1040007	7 Litre	3
PKES1040010	10 Litre	
PKES1040020	20 Litre	
PKES1040205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN
- ✓ ACEA A3/B4
- ✓ MB 229.3
- ✓ PSA B71 2300
- ✓ VW 502 00/505 00
- ✓ Renault RN 0710

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 23 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982