

PEAK SUPER RED GREASE

EXTREME PRESSURE LITHIUM GREASE - NLGI 2

DESCRIPTION & APPLICATION:

Peak Super Red Grease (EP2) is a premium, multipurpose lithium based NLGI No. 2 grease, designed to meet the demands of the most hostile grease applications and conditions.

Peak Super Red Grease Recommended for use in most types of automotive, agricultural and industrial applications including heavy-duty service where high loads are encountered, rolling element bearings, plain bearings, gears and couplings. Also suitable for use in steel mills, underground tunnelling, mining and ore crushing plants.

BENEFITS:

- High degree of thermal and mechanical stability
- High load carrying capacity which protects equipment against extreme loading
- Reduced oil separation
- Excellent EP and anti-wear properties resulting in reduced bearing component wear
- Good water resistance against water spray & washout
- Provides superior protection against rust and corrosion

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
NLGI Grade	2
Soap/Thickener Type	Lithium
Dropping point °C	195
Oil Viscosity 40°C cSt	300
4 Ball Weld Load, Kg	355
Operating Temperature Range °C	-20°C to 140°C
Colour	Red

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGXSRL450	450 GM	12
PKGXSRL02.5	2.5 KG	
PKGXSRL020	20 KG	
PKGXSRL055	55 KG	
PKGXSRL180	180 KG	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 26 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982