

# PEAK SEMI SYNTHETIC TWO STROKE OIL

## SEMI SYNTHETIC TWO STROKE OIL

### DESCRIPTION & APPLICATION:

PEAK TWO STROKE OIL is formulated with low ash levels and mixes easily with petrol.

PEAK TWO STROKE OIL is suitable as a lubricant in air-cooled two stroke engines typically found in lawn mowers, brush cutters & chainsaws. May also be used in other small air-cooled two stroke engines at the manufacturers recommended fuel/oil dilution rates.

### BENEFITS:

- Keeps the engine clean by preventing ring sticking
- Meets ISO- L- EGD, TISI Level
- Prevents piston deposits
- Protects against plug fouling and exhaust deposits

**NOTE:** Not recommended for marine applications where NMMA TC-W3 is specified.

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	0.861
Viscosity 40°C cSt	64.11
Viscosity 100°C cSt	9.49
Viscosity Index	128.4
Flash Point °C	>100
Colour	Blue

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKOSTS020	20 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ JASO FD
- ✓ TISI
- ✓ API TC
- ✓ ISO- L- EGD

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 9 February 2021

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

#### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982