



PEAK SUPER OUTBOARD OIL

OUTBOARD 2 STROKE OIL

DESCRIPTION & APPLICATION:

PEAK SUPER OUTBOARD OIL is a premium performance TC-W3 marine outboard two stroke oil formulated using an ashless additive system and high flash solvent to ensure excellent mixing with fuel. It is recommended for all high performance water-cooled two stroke engines, both oil injected and using premix fuel systems.

PEAK SUPER OUTBOARD OIL has an advanced additive pack which includes a selected synthetic component for enhanced lubricity, which protects against wear under extreme operating conditions. The ashless formulation will ensure that spark plug fouling is minimised and ash induced deposits in the combustion chamber are eliminated.

BENEFITS:

- Delivers superior piston cleanliness and protection against ring sticking
- Enhanced lubricity protects against wear under extreme operating conditions
- Self-mixing with both leaded and unleaded petrol

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.872
Viscosity 40°C cSt	44.0
Viscosity 100°C cSt	7.2
Viscosity Index	125
Flash Point °C	75

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE
PKOB020	20 Litre
PKOB205	205 Litre
PKOB000	1000 Litre

SPECIFICATIONS & PERFORMANCE LEVEL:

✓ NMMA TC-W3

✓ API TD

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 1 March 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982