



PEAK AC 68 COMPRESSOR OIL

AIR COMPRESSOR OIL

DESCRIPTION & APPLICATION:

PEAK AC 68 is a premium compressor oil formulated to provide outstanding lubrication, performance and protection of rotary sliding vane and screw air compressors.

PEAK AC 68 uses a premium additive package to deliver exceptional performance for compressors operating at up to 100°C discharge temperatures and with up to 4,000 hour oil drain periods (with lubricant analysis monitoring and where allowed by manufacturers).

BENEFITS:

- Excellent chemical and thermal stability ensuring good service life
- Outstanding wear protection – protecting the rotating components in screw compressors
- Reduced foaming and exceptional cleanliness and filtering ability even when subjected to moisture or water contamination
- Anti-clogging property which extends the life of the separating filter elements

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.878
Kinetic Viscosity @ 40°C cSt	67.5
Kinetic Viscosity @ 100°C cSt	8.8
Viscosity Index	102
Flash Point °C	>210
ASTM Colour	L 0.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIAM068001	1 Litre	6
PKIAM068005	5 Litre	4
PKIAM068020	20 Litre	
PKIAM068205	205 Litre	
PKIAM0681000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 6743-3:2003 I-DAH

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 15 August 2021

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982