

PEAK PROCESS OIL 32

PARAFFINIC MINERAL OIL

DESCRIPTION & APPLICATION:

PEAK PROCESS OIL 32 is a medium viscosity hydro-processed paraffinic process oil. It has an extremely low sulphur, nitrogen, and aromatic content which delivers excellent thermal and oxidation stability.

PEAK PROCESS OIL 32 is used in a variety of applications: as an extender in the plastics, rubber and adhesive industry, a carrier in chemical processing, in the manufacture of finished lubricants and in many other applications.

BENEFITS:

- Exceptional Oxidation stability
- Low aromatic and Sulphur content
- Good viscosity-temperature characteristics
- Low volatility

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.852
Viscosity @ 40°C cSt	29.8
Viscosity @ 100°C cSt	5.3
Viscosity Index	110
Flash Point °C	>210

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIPRO032020	20 Litre	
PKIPRO032205	205 Litre	
PKIPRO0321000	1000 Litre	

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 26 July 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982