

STELLA™ PLUS GREASE

FOOD GRADE ALUMINIUM COMPLEX GREASE

DESCRIPTION & APPLICATION:

STELLA™ PLUS GREASE are designed to cover a wide range of food safe applications, encompassing extremes of temperature, wet and saturated environments, heavily loaded applications and where there is a presence of dust and other contaminants.

STELLA™ PLUS GREASE are NSF H1 registered for use where incidental contact with food may occur in food, drink and pharmaceutical processing and packaging equipment

STELLA™ PLUS GREASE contain extreme pressure and anti-wear additives to provide a high degree of load carrying performance. Suitable for all plain and anti-friction bearings as well as sliding surfaces.

BENEFITS:

- Provide long term lubrication at high temperatures
- Excellent anti-wear performance prolonging component life
- Exceptional water resistance providing lasting protection against corrosion
- Safe for use in HACCP Certified Food and Packaging Manufacturing Plants

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE
PKGAFP2	400g, 18kg
PKGAFP1	400g

TYPICAL CHARACTERISTICS*:

TEST	PLUS 1	PLUS 2
Appearance	Off White Tacky	
NLGI Classification	1	2
Thickener	Aluminium Complex	
Base Oil Type	Blend of Synthetic Oils	
Drop Point °C	>230	
4 Ball Weld Load kg	450	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ NSF H1 registered

Stella™ is a trademark of Food Grade Oils Pty Ltd

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 19 August 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982