

PEAK 5W40

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W40 is formulated to meet ACEA C3, MB 229.51 and GM Dexos2™ making this oil suitable for diesel vehicles with a DPF (diesel particulate filter) that require low a SAPS (Sulphated Ash, Phosphorus & Sulphur) engine oil.

PEAK 5W40 is suitable for modern diesel vehicles fitted with Diesel Particulate Filters (DPF), this product is also recommended for petrol and hybrid vehicles making this a high-quality multi-vehicle engine oil.

BENEFITS:

- Excellent soot and sludge control
- Extended engine oil drain intervals.
- Outstanding low temperature performance for reduced wear on start-up.
- Low SAPS (Sulphated Ash, Phosphorus and Sulphur).

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.860
Viscosity 40°C cSt	98.7
Viscosity 100°C cSt	15.5
Viscosity Index	166.7
Flash Point °C	>215
Sulphated Ash	0.8
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEFC3540001	1 Litre	6
PKEFC3540005	5 Litre	4
PKEFC3540010	10 Litre	
PKEFC3540020	20 Litre	
PKEFC3540205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN / CF
- ✓ ACEA C3
- ✓ MB-Approval 229.31/229.51
- ✓ VW 502 00 / 505 01
- ✓ BMW LL-04 (Long Life -04)
- ✓ GM Dexos2™
- ✓ Porsche A40
- ✓ Renault RN0700 / RN0710
- ✓ MB Approval 226.5

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982