

PEAK 5W30 FE

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W30 FE is a full synthetic engine oil that is specifically designed for fuel economy with premium quality additives for engine protection and sludge control.

PEAK 5W30 FE is suitable for petrol, light duty diesel engines and diesel vehicles fitted with a DPF where the specifications ACEA A5/B5, Ford WSS M2C-913D / C / B are required.

BENEFITS:

- Outstanding thermal and oxidation stability for longer oil life
- Enhanced frictional properties for less wear and fuel consumption
- Maintains viscosity and performance even at extreme temperatures
- Excellent flow characteristics even at very low temperatures

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.851
Viscosity 40°C cSt	53.8
Viscosity 100°C cSt	9.9
Viscosity Index	172
Flash Point °C	>210
Sulphated Ash	1.1
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKED530F005	5 Litre	4
PKEF530F010	10 Litre	
PKEF530F020	20 Litre	
PKEF530F205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SL
- ✓ ACEA A5/B5
- ✓ Ford WSS M2C-913D / C / B
- ✓ Renault RN 0700
- ✓ STJLR.03.5003

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 January 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982