

PEAK 5W30 D1

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W30 D1 is a full synthetic engine oil that uses premium quality full synthetic base oil and high-quality additives making this engine oil suitable for vehicles requiring API SP, Dexos1™ Gen 2 and ILSAC GF-6.

PEAK 5W30 D1 is designed for use in modern naturally aspirated, supercharged & turbocharged petrol, low emission engines and hybrids vehicles. Recommended for passenger cars, 4WD's and light commercial vehicles where Petrol, E10 and E85 fuels are used.

BENEFITS:

- Improved power and engine responsiveness
- Excellent Deposit Control
- Very high shear stability with a fast-flowing formula
- Specifically formulated for use in GDI and TGD1 engines

TYPICAL CHARACTERISTICS*:

| TEST | METHOD | TYPICAL VALUE |
|---------------------------------|------------|---------------|
| Density 15° C g/cm ³ | ASTM D7042 | 0.850 |
| Kinetic Viscosity @ 40°C cSt | ASTM D7042 | 54.97 |
| Kinetic Viscosity @ 100°C cSt | ASTM D7042 | 10.15 |
| Viscosity Index | ASTM D2270 | 174 |
| Flash Point °C | ASTM D92 | >215 |
| Colour | ASTM 1500 | L 2.5 |

PRODUCT SIZES:

| PRODUCT CODE | PACK SIZE | CTN QTY |
|--------------|-----------|---------|
| PKEFD1530005 | 5 Litre | 4 |
| PKEFD1530010 | 10 Litre | |
| PKEFD1530020 | 20 Litre | |
| PKEFD1530205 | 205 Litre | |

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SP
- ✓ ILSAC GF-6
- ✓ Dexos1™ Gen 2

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 20 October 2020

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982