



PEAK DIESEL EXHAUST FLUID

ADBLUE®- Aqueous Urea Solution

DESCRIPTION & APPLICATION:

PEAK DIESEL EXHAUST FLUID – AdBlue® is a high purity Nitrogen Oxide (NOx) reducing agent for diesel engines (including marine) equipped with Selective Catalytic Reduction (SCR) technology. The catalytic reaction transforms the NOx's to Nitrogen and Water.

BENEFITS:

- Reduces the levels of noxious emissions to almost zero
- Improves fuel economy
- Non toxic & safe to handle

NOTE: DO NOT add to fuel or fuel tank. Pour into Diesel Exhaust Fluid Reservoir only. Storage life is 18 months from production date if kept in closed containers and at storage temperatures below 25°C.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Appearance	Colourless Liquid
Density 20°C g/cm ³	1.09
Urea Content %	32.4
Refractive Index @ 20°C	1.38

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKADDEF010	10 Litre	
PKADDEF020	20 Litre	
PKADDEF200	200 Litre	
PKADDEF1000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ AUS 32
- ✓ ISO 22 241
- ✓ DIN 70070
- ✓ FORD WSS-M99C130-A

AdBlue® is a trademark of Verband der Automobilindustrie e.V.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 16 March 2023



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982