

PEAK HAMMER GREASE

ALUMINIUM COMPLEX GREASE - NLGI 2

DESCRIPTION & APPLICATION:

PEAK HAMMER Grease is an advanced Aluminium Complex NLGI No. 2 heavy-duty EP grease that is specifically designed for the lubrication of power hammers. The addition of Copper, Graphite and Moly make it especially suitable for threaded connections on pipes, flanges and threaded fasteners.

PEAK HAMMER Grease can also be used for anti-seize applications where temperatures can reach 1100°C and/or in high corrosive environments such as Chemical Manufacturing or off-shore exploration/production .

BENEFITS:

- Excellent thermal and mechanical stability
- Excellent water resistance to water spray & washout and does not deteriorate even in the presence of salt water or extreme conditions
- Resistant to both acidic & caustic materials
- Prevents seizure and galling during assembly
- Provides superior protection allowing for parts to be reused after dismantling

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
NLGI Grade	2
Soap/Thickener Type	Aluminium Complex
Dropping point °C	>260
Lubricating Solids	Copper, Graphite and Moly
Solids Content %	10
Anti-seize Temperature Range °C	-30°C to 1100°C
Colour	Dark Copper

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKHAMM.450	450G	20

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 24 January 2023

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982