



PEAK TORQUE FLUID 10W

PREMIUM MINERAL TRANSMISSION OIL

DESCRIPTION & APPLICATION:

PEAK TORQUE FLUID 10W is a heavy-duty transmission fluid formulated for use in power-shift transmissions, drive trains and hydraulic systems in off-highway, earthmoving, mining, logging and farm applications. Suitable to be used in Caterpillar TO-4 and TO-2 applications, Allison C4 and where a monograde SAE 10 transmission oil is specified.

PEAK TORQUE FLUID 10W extends clutch life and assists to eliminate transmission slippage, reduce brake chatter, protect against corrosion and rust. It has excellent compatibility with seals and frictional material, and superior anti-foam characteristics.

BENEFITS:

- Protects against rust and corrosion
- Prevents transmission slippage
- Longer oil life through enhanced oxidation stability
- Excellent wear protection

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.863
Viscosity 40°C cSt	34.60
Viscosity 100°C cSt	6.0
Viscosity Index	120
Flash Point °C	>210
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKGMTF10020	20 Litre	
PKGMTF10205	205 Litre	
PKGMTF101000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Allison C-4 (obsolete)
- ✓ API GL-3
- ✓ Caterpillar TO-4
- ✓ DANA Powershift
- ✓ Komatsu Dresser
- ✓ Komatsu KES 07.868.1
- ✓ ZF TE-ML 03C

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 20 January 2023



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982