

PEAK ECOSYN ULTRA AC 46

SYNTHETIC COMPRESSOR OIL

DESCRIPTION & APPLICATION:

PEAK ECOSYN ULTRA AC 46 is an advanced synthetic compressor oil specifically formulated to deliver outstanding lubrication, performance and protection of rotary sliding vane and screw air compressors.

PEAK ECOSYN ULTRA AC 46 uses a premium additive package to deliver exceptional performance for compressors operating at up to 100°C discharge temperatures and with up to 8,000 hour oil drain periods (with lubricant analysis monitoring and where allowed by manufacturers).

BENEFITS:

- Excellent chemical and thermal stability ensuring good service life
- Outstanding wear protection – protecting the screws against wear and corrosion.
- Reduced foaming and exceptional cleanliness and filtering ability even when subjected to moisture or water contamination.
- Anti-clogging property which extends the life of the separating filter elements.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.839
Kinetic Viscosity @ 40°C cSt	46.0
Kinetic Viscosity @ 100°C cSt	7.7
Viscosity Index	138
Flash Point °C	>250
Pour Point °C	-48

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIAF046U020	20 Litre	
PKIAF046U205	205 Litre	
PKIAF046U1000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 6743-3:2003 I-DAJ

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 15 August 2021

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982