



PEAK AC 32 COMPRESSOR OIL

AIR COMPRESSOR OIL

DESCRIPTION & APPLICATION:

PEAK AC 32 is a premium compressor oil formulated to provide outstanding lubrication, performance and protection of rotary sliding vane and screw air compressors.

PEAK AC 32 uses a premium additive package to deliver exceptional performance for compressors operating at up to 100°C discharge temperatures and with up to 4,000 hour oil drain periods (with lubricant analysis monitoring and where allowed by manufacturers).

BENEFITS:

- Excellent chemical and thermal stability ensuring good service life
- Outstanding wear protection – protecting the rotating components in screw compressors
- Reduced foaming and exceptional cleanliness and filtering ability even when subjected to moisture or water contamination
- Anti-clogging property which extends the life of the separating filter elements

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.856
Kinetic Viscosity @ 40°C cSt	30.4
Kinetic Viscosity @ 100°C cSt	5.2
Viscosity Index	100
Flash Point °C	>210
ASTM Colour	L 0.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIAM032020	20 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 6743-3:2003 I-DAH

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 15 August 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982