



PEAK 5W30 C3

FULL SYNTHETIC ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK 5W30 C3 is a mid-SAPS synthetic engine oil formulated to meet the demands and fuel efficiency expectations of the latest petrol and diesel engines, suitable for use where API SP, ACEA C3, MB 229.52 are required.

PEAK 5W30 C3 is recommended for use in modern turbocharged, supercharged and naturally aspirated petrol engines, diesel engines fitted with Diesel Particulate Filters (DPF) and hybrid vehicles.

* OV 0401547 is suitable in all places where Dexos2 is recommended.

BENEFITS:

- Excellent soot and sludge control
- Extended engine oil drain intervals.
- Mid SAPS (Sulphated Ash, Phosphorus and Sulphur).
- Outstanding low temperature performance for reduced wear on start-up.

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.854
Viscosity 40°C cSt	69.0
Viscosity 100°C cSt	11.4
Viscosity Index	161
Flash Point °C	>215
Sulphated Ash	0.8
Colour	L 2.0

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKEFC3530001	1 Litre	6
PKEFC3530005	5 Litre	4
PKEFC3530007	7 Litre	3
PKEFC3530010	10 Litre	
PKEFC3530020	20 Litre	
PKEFC3530205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SP
- ✓ ACEA C3
- ✓ ACEA C2
- ✓ MB 229.52
- ✓ MB 229.31/229.51
- ✓ BMW LL-04 (Long Life -04)
- ✓ OV 0401547 (supersedes dexos2)

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 14 October 2021



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982