

# PEAK LONG LIFE COOLANT CONCENTRATE

## 5 YEAR 250,000KM DRAIN INTERVAL

### DESCRIPTION & APPLICATION:

PEAK Long Life Coolant Concentrate is an Ethylene Glycol OAT based coolant formulated with a proprietary corrosion inhibitor package. This is Silicate, Borate, Phosphate, Amine and Nitrate free providing ideal protection for of all engine metals including aluminium and ferrous alloys for up to 5 years.

PEAK Long Life Coolant Concentrate provides anti-freeze and anti-boil additives that provide the best balance of protection against freezing, corrosion and overheating. Suitable for use in diesel trucks, buses, agricultural and earthmoving applications as well as passenger cars and stationary engines.

### BENEFITS:

- Silicate, Borate, Phosphate, Amine and Nitrite free
- Excellent choice for use in mixed fleets
- Long drain intervals
- Compatible with all plastics, rubbers, seals and aluminium

Available in Blue, Green and Red

**NOTE:** Not to be used in concentrated form.

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	1.1
Boiling Point °C (not mixed)	170
Flash Point °C (not mixed)	> 120
Colour	Blue / Yellow

### DOSE RATE - FREEZING POINT - BOILING POINT

Mixture ratio	33%	50%
Freezing Point °C	-19	-37
Boiling Point °C	125	127

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKROLLBC001 (Blue)	1 Litre	12
PKROLLBC005 (Blue)	5 Litre	4
PKROLLBC020 (Blue)	20 Litre	
PKROLLGC001 (Green)	1 Litre	12
PKROLLGC005 (Green)	5 Litre	4
PKROLLGC020 (Green)	20 Litre	
PKROLLGC205 (Green)	205 Litre	
PKROLLRC001 (Red)	1 Litre	12
PKROLLRC005 (Red)	5 Litre	4
PKROLLRC020 (Red)	20 Litre	
PKROLLRC205 (Red)	205 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

- |               |                                    |                    |
|---------------|------------------------------------|--------------------|
| ✓ ASTM D-3306 | ✓ AS/NZS 2108.1Coolant Type A 2004 | ✓ GM1825M/ 1899M   |
| ✓ ASTM D-6210 | ✓ John Deere JDM H24B1 / C1        | ✓ Cummins 90T8-4   |
| ✓ ASTM D-4985 | ✓ Ford WSS-M97B44-C                | ✓ J.I. Case JIC501 |
| ✓ SAE J1034   |                                    |                    |

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

### PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned  
Since 1982



Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 27 September 2021

\* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

**PEAK LUBRICANTS PTY LTD**

**HEAD OFFICE:** 224-230 South Gippsland Highway, Dandenong South VIC 3175

**PHONE:** 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256

**EMAIL:** tech@peakoil.com.au / **WEB:** www.peakoil.com.au

**ABN:** 74 8875 10101



**Proudly Australian Owned  
Since 1982**