

PEAK NEAT CUT 22

NEAT CUTTING OIL

DESCRIPTION & APPLICATION:

PEAK NEAT CUT 22 is an inactive type cutting oil formulated with refined naphthenic base oils. It is an excellent dual-purpose cutting and lubricating oil for higher speed machining of free cutting steels; brass, aluminium, copper, etc. in multiple spindle automatics.

PEAK NEAT CUT 22 acts as both a machine lubricant and a cutting oil where a lower viscosity oil is required. For eg. higher speed machining of free cutting steels such as brass, aluminium, copper and other softer type metals.

FEATURES & BENEFITS:

- Serves as both a machine lubricant and a cutting oil
- Longer tool life tool life and improved surface finish,
- Non active formulation makes it suitable for copper based alloys

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.902
Kinetic Viscosity @ 40°C cSt	22.0
Flash Point °C	>150

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKICMNC22020	20 Litre	
PKICMNC22205	205 Litre	

APPLICATION :

- Used neat

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 13 July 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982