



PEAK DRAWING OIL EC3

DRAWING AND STAMPING FLUID

DESCRIPTION & APPLICATION:

PEAK DRAWING OIL EC3 is a semi-synthetic fluid based on chlorinated paraffin for use where extreme pressure operations are encountered, particularly on brass and stainless steels.

PEAK DRAWING OIL EC3 is viscous and is satisfactory for pumping and spraying.

FEATURES & BENEFITS:

- Can be used neat for metal drawing, stamping and hand application for machining operations.
- Can be diluted with other cutting oils or other hydrocarbons for other drawing and machining operations
- Excellent Die protection
- Improvement in surface finish

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	1.15
Kinetic Viscosity @ 40°C cSt	190
Active Ingredient	Chlorine

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKICMDEC3020	20 Litre	

APPLICATION :

- Use undiluted for metal drawing, stamping and hand application for machining operations.
- The product can be applied using a pump or spray.

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 14 January 2022

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982