



PEAK SYN TORA 150

FULL SYNTHETIC INDUSTRIAL GEAR OIL

DESCRIPTION & APPLICATION:

PEAK SYN TORA 150 is an advanced synthetic industrial gear oil which delivers outstanding performance under severe operating conditions such as high loads and wide temperature variations. It has been specially developed to reduce friction and deliver long service life.

PEAK SYN TORA 150 is designed to resist micro-pitting and maintain system efficiency.

BENEFITS:

- Long service life reduces maintenance costs
- Excellent wear and corrosion protection
- High film strength for superior wear protection and load carrying capability even under shock loading conditions
- Outstanding flow properties over a wide temperature range enhances the efficiency of industrial gear systems

TYPICAL CHARACTERISTICS*:

TEST	METHOD	TYPICAL VALUE
Density 15° C g/cm ³	ASTM D7042	0.878
Viscosity @ 40°C cSt	ASTM D7042	145
Viscosity @ 100°C cSt	ASTM D7042	20
Viscosity Index	ASTM D2270	159
Flash Point °C	ASTM D92	>230

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIGF0150020	20 Litre	
PKIGF0150205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ US Steel 224
- ✓ AGMA 9005-F16
- ✓ DIN 51517-3 (CLP)
- ✓ David Brown S1.53.106

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 29 March 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982