



# PEAK SYNGEAR ULTRA 75W140

## FULL SYNTHETIC GEAR OIL

### DESCRIPTION & APPLICATION:

PEAK SYNGEAR ULTRA 75W140 is a full synthetic gear oil meeting API GL-5 specially formulated for use in automotive light duty and heavy-duty axles and heavy duty non-synchronized transmissions.

PEAK SYNGEAR ULTRA 75W140 is recommended for high performance heavy duty applications including vehicles with limited slip differential. PEAK SYNGEAR ULTRA 75W140 is also suitable where an SAE 140, 80W140 and 85W140 hypoid gear oil is recommended.

### BENEFITS:

- Superior wear protection for prolonged equipment life.
- Excellent shear stability allowing for longer lubricant life resulting in extended drain intervals
- Outstanding resistance to corrosion and oil degradation.

### TYPICAL CHARACTERISTICS\*:

TEST	TYPICAL VALUE
Density 15° C g/cm <sup>3</sup>	0.870
Viscosity 40°C cSt	192.1
Viscosity 100°C cSt	27.49
Viscosity Index	181.7
Flash Point °C	>205

### PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKG75140002.5	2.5 Litre	6
PKG75140020	20 Litre	
PKG75140205	205 Litre	

### SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API GL-5
- ✓ API MT-1
- ✓ MACK GO-J PLUS
- ✓ ARVIN MERITOR 0-7-M/Q/R
- ✓ FORD WSL-M2C192A
- ✓ MB 235.61
- ✓ ZF ML-12B
- ✓ PG-2 LIMITED SLIP
- ✓ MIL-PRF-2105D / MIL-PRF-2105E
- ✓ SAE J2360
- ✓ DAF
- ✓ SCANIA ST:0
- ✓ ZF ML-16G/F
- ✓ ZF ML-07A

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

\*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 12 December 2022



**PEAK LUBRICANTS PTY LTD**  
**HEAD OFFICE:** 224-230 South Gippsland Highway, Dandenong South VIC 3175  
**PHONE:** 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256  
**EMAIL:** tech@peakoil.com.au / **WEB:** www.peakoil.com.au  
**ABN:** 74 8875 10101



Proudly Australian Owned  
Since 1982