



PEAK HEAT TRANSFER 32

HEAT TRANSFER FLUID

DESCRIPTION & APPLICATION:

PEAK Heat Transfer Oil 32 is based on severely hydrocracked base oils chosen for their ability to resist thermal cracking and chemical oxidation at high temperatures, providing superior performance in heat transfer systems.

PEAK Heat Transfer Oil 32 provides extended oil life, provided efficient fluid heating and good pump circulation is ensured.

PEAK Heat Transfer Oil 32 is used in enclosed circulated heat transfer systems. It can be used in high temperature continuous heat transfer equipment with the following application limits:

Closed System: Maximum bulk temperature = 320°C

Open System: Maximum bulk temperature = 180°C

A well-designed heat transfer system along with oil condition monitoring can extend the life of the oil by many years.

BENEFITS:

- Low viscosity delivers excellent fluidity and heat transfer over a wide temperature range.
- Good thermal and oxidation stability characteristics permit higher operating temperatures and provide long fluid life.
- Being non-corrosive with a relatively high solvency helps reduce deposit formation keeping internal surfaces cleaner for longer.
- Low vapour pressure minimises the formation of volatile decomposition products.

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE
PKIHT032020	20 Litre
PKIHT032205	205 Litre
PKIHT0321000	1000 Litre

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.854
Viscosity 40°C cSt	28.8
Viscosity 100°C cSt	5.3
Viscosity Index	118
Flash Point °C	>210

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ Meets DIN 51522 requirements

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

Published 11 February 2021

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982