

PEAK JAY 10

PREMIUM MINERAL CIRCULATING OIL

DESCRIPTION & APPLICATION:

PEAK JAY 10 is a low viscosity high quality mineral based machine circulating and lubricating oil. It will provide protection against rusting, oxidation and corrosion and is suitable for lubricating high speed bearings, needles and spindles requiring a non-zinc anti wear oil.

PEAK JAY 10 is designed to meet specifications requiring a premium quality, light viscosity oil for applications running at high speeds such as those found in high speed frames and automated machine tools

BENEFITS:

- Excellent wear and corrosion protection provides high resistance to oxidation and helps to prolong oil life and lower maintenance costs
- Low viscosity for the smooth running of high speed machine elements and to minimise heat build-up through frictional energy losses.
- Non-Zinc anti-wear additives make it suitable for use in circulating systems where silver plated components may be present

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm³	0.832
Viscosity @ 40°C cSt	11.8
Viscosity @ 100°C cSt	2.95
Viscosity Index	100
Flash Point °C	>150

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIMM010020	20 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

✓ Cincinnati Milacron P62

 $Health, safety\ and\ environmental\ information\ is\ provided\ on\ the\ Safety\ Data\ Sheet\ (SDS)\ for\ this\ product.$

Published 27 September 2021 is correct at time of publishing.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.





ABN: 74 8875 10101