

PEAK AC 150 COMPRESSOR OIL

AIR COMPRESSOR OIL

DESCRIPTION & APPLICATION:

PEAK AC 150 is a premium compressor oil formulated to provide outstanding lubrication, performance and protection of high pressure reciprocating (piston) compressors operating at air discharge temperatures of up to 220°C and rotary screw air compressors (oil flooded or oil injected) single or two-stage compressors operating at pressures of up to 20 bar and with air discharge temperatures of up to 100°C.

BENEFITS:

- Excellent chemical and thermal stability ensuring good service life
- Outstanding wear protection
- Reduced foaming and exceptional cleanliness and filtering ability
- Anti-clogging property which extends the life of the separating filter elements

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.876
Kinetic Viscosity @ 40°C cSt	151.4
Kinetic Viscosity @ 100°C cSt	15.2
Viscosity Index	101
Flash Point °C	>210
ASTM Colour	L 1.5

PRODUCT SIZES:

PRODUCT CODE	PACK SIZE	CTN QTY
PKIAM0150020	20 Litre	
PKIAM0150205	205 Litre	
PKIAM01501000	1000 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ ISO 6743-3A:2003 L-DAB
- ✓ DIN 51506 VBL

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.

* Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 15 August 2021

PEAK LUBRICANTS PTY LTD

HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175

PHONE: 03 9799 0977 / TECHNICAL LUBELINE: 1300 722 256

EMAIL: tech@peakoil.com.au / WEB: www.peakoil.com.au

ABN: 74 8875 10101



Proudly Australian Owned
Since 1982