



PEAK GAS 15W40

PREMIUM MINERAL ENGINE OIL

DESCRIPTION & APPLICATION:

PEAK GAS 15W40 is a high quality engine oil formulated with Premium mineral base oils and high-performance additives making it suitable for engines requiring API SN and ACEA A3 / B4.

PEAK GAS 15W40 is recommended for dual fuel engines (multivalve and turbo) with or without a catalytic converter. This product is suitable for diesel vehicles.

BENEFITS:

- Engine seals stay soft and pliable to minimise and reduce oil leakages
- Excellent detergent additives to improved engine cleanliness
- Outstanding thermal and oxidation stability

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.8
Viscosity 40°C cSt	110.8
Viscosity 100°C cSt	14.9
Viscosity Index	139.6
Flash Point °C	>195
Colour	L3.0

PRODUCT SIZES

PRODUCT CODE	PACK SIZE	CTN QTY
PKEMGAS020	20 Litre	
PKEMGAS205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- ✓ API SN
- ✓ ACEA A3/B4
- ✓ ACEA A3/B3-12
- ✓ VW 501 01/505 00

Health, safety and environmental information is provided on the Safety Data Sheet (SDS) for this product.
*Typical characteristics are provided as a guide only and are subject to manufacturing tolerances. They however do not constitute any legal liability. Information is correct at time of publishing.

Published 12 July 2022



PEAK LUBRICANTS PTY LTD
HEAD OFFICE: 224-230 South Gippsland Highway, Dandenong South VIC 3175
PHONE: 03 9799 0977 / **TECHNICAL LUBELINE:** 1300 722 256
EMAIL: tech@peakoil.com.au / **WEB:** www.peakoil.com.au
ABN: 74 8875 10101



Proudly Australian Owned
Since 1982